

2000 Series Specifications

Cylinders	4 in line
Bore	84 mm.
Stroke	88.5 mm.
Cylinder capacity	1962 cc.
Compression ratio	9.0
Brake horsepower @ 5800 rpm	129 SAE net

Gear ratios	Gearbox
1st	3.30
2nd	1.99
3rd	1.35
4th	1.00
5th	.79

Tires	165 HR 14 on 5 1/2" wide wheels
Electrical system	12 volts
Fuel capacity (Berlina & GT Veloce)	14 gallons
(Spider Veloce)	13.4 gallons

Carburetion: Alfa Romeo-Spica fuel injection.

Valve Timing: V-overhead valves operated by dual overhead camshafts. Sodium-cooled exhaust valves.

Clutch: Hydraulically operated.

Gearbox: 5 fully synchronized forward speeds and reverse.

Ignition: Golden Lodge spark plugs.

Electrical System: 12 volt, 35 ampere alternator; 60 Ah battery.

Front Suspension: Independent front wheel suspension secured by inclined transverse A arms. Coil springs and telescopic hydraulic double-acting shock absorbers. Transverse anti-roll bar.

Rear Suspension: Coil springs and coaxially-mounted telescopic hydraulic double-acting shock absorbers. Transverse anti-roll bar.

Rear Axle: Anchored to body structure by two trailing arms and upper torque reaction T. Transverse anchorage fitted with rubber bushes on frame and axle.

Steering: Recirculating ball or worm and roller.

Brakes: Power-assisted 4-wheel disc brakes with safety dual circuits and pressure modulator on rear brakes. Hand brake operates via separate drums on rear wheels.

STANDARD EQUIPMENT

- Alfa Romeo fuel injection
- 4-wheel power disc brakes
- 5-forward speed gearbox
- Texalfa upholstery
- Reclining front seats
- Hand throttle
- Tachometer
- Trip meter
- Fuel gauge with warning light
- Oil pressure gauge with warning light
- Automatic cigarette lighter
- Heater with 2-speed blower and warning light
- Windshield washer
- Brake fluid level warning light
- Hand brake warning light
- Brake modulator
- Sealed cooling system
- Tool kit
- 60 Ah battery
- Fully carpeted trunk
- Under-hood and trunk lights
- Parking lamp warning light
- Fog lamps (GT Veloce only)
- Electric clock (Berlina only)
- Mahogany dashboard paneling (Berlina & GT Veloce only)
- Electrically heated rear window (Berlina & GT Veloce only)
- Wood steering wheel (Spider Veloce & GT Veloce only)



2000 Spider Veloce®

Beneath elegant new Kamm-tail styling by Pininfarina nestles the legendary, race-refined Alfa D.O.H.C. Plus gearbox, suspension, brakes and steering producing handling, road-holding and cornering capabilities to satisfy the most demanding performance enthusiast. Top speed: 118 mph.

Wheelbase	88 3/4"
Front track	52 1/8"
Rear track	50 1/4"
Overall length	161 1/2"
Overall width	64 1/2"
Overall height	50 1/2"
Curb weight	2292 lb



2000 GT Veloce®

Outstanding styling by Bertone, outstanding performance by Alfa Romeo. Result: a true *gran turismo* car offering race-refined performance, handling and safety in a richly appointed, classically styled coupe. Top speed: 118 mph.

Wheelbase	92 1/2"
Front track	52 1/8"
Rear track	50 1/4"
Overall length	161"
Overall width	62 1/2"
Overall height	51 1/2"
Curb weight	2292 lb



2000 Berlina

Performance so unexpected in a family car that many enthusiasts consider it "a racing car in disguise." Bertone styling. Rigid-unit body construction. Same D.O.H.C. engine, transmission, brakes and running gear as every other Alfa—in a spacious and comfortable four door car. Top speed: 112 mph.

Wheelbase	101 1/2"
Front track	52 1/8"
Rear track	50 1/4"
Overall length	172 1/4"
Overall width	88 1/2"
Overall height	56 1/2"
Curb weight	2442 lb

